

What oil should be used for the oiler of the yt28 rock drill

Which lubricator is used in Rock Drill yt28?

The Rock Drill is equipped with lubricator FY200C. Secoroc YT28 is intended to be used together with pusher leg FT160BC and FT160BD for different tunneling and work conditions. It is also designed for dry drilling or wet drilling mounted on rigs. Specification Pneumatic rock drill YT28

Is yt28 suitable for drilling rocks?

YT28 is suitable for drilling rocks with a hardness of $f = 8 \sim 18$. Page 4 Air-Leg Specifications Weight Length Feed Length Model (Kg) (mm) (mm) FT160 1668 1338 Installation and Lubrication Size air supply line to ensure tool's maximum operating pressure (P_{MAX}) at tool inlet.

What is a yt28 pusher leg rock drill used for?

Rock drilling tools manufacturer ProDrill: Model No. YT28 Pusher Leg Rock Drills are applied for underground mining, drifting. YT28 Air-leg Rock Drill most fit for drilling horizontal and inclined blast holes in medium-hard and hard rock with a hardness of $f = 8 \sim 18$. It may also be used with for making roof-bolting holes.

What is yt28 air-leg rock drill used for?

YT28 Air-leg Rock Drill most fit for drilling horizontal and inclined blast holes in medium-hard and hard rock with a hardness of $f = 8 \sim 18$. It may also be used with for making roof-bolting holes. The drill is an important instrument in mining, railway, communication and water conservancy projects.

How do you use a rock drill?

Operation Using the rock drill for the first time When the rock drill arrives from the factory, the inside of the tool is coated with heavy oil to prevent corrosion. After unpacking and installing the tool, pour a small amount of lubrication oil into the air connection and operate the tool on partial throttle to clean the interior. 4.

How do you lubricate a rock drill & pusher leg?

The rock drill and pusher leg are lubricated with oil mixed with compressed air, which is taken to the parts that need continuous lubrication. Oil is metered into the compressed air using the FY250 lubricator connected to the air line.

The air-leg rock drill is installed on the air leg for operation, and the air leg can play the role of support and propulsion, which reduces the labor intensity of ...

The air-leg rock drill is installed on the air leg for operation, and the air leg can play the role of support and propulsion, which reduces the labor intensity of the operator, and the rock drilling ...



What oil should be used for the oiler of the yt28 rock drill

The YT28 is an air percussive rock drill designed for drilling in rock formations. The FY200C is an oil liner for lubrication. The FT160A is an air-leg used to support drilling equipment during ...

The rock drill and pusher leg are lubricated with oil mixed with compressed air, which is taken to the parts that need continuous lubrication. Oil is metered into the compressed air using the ...

YT28 air-leg rock drill is a new type of rock drill is widely used in quarrying, mining, tunneling, and drilling blast holes in various rock drilling ...

The weight of the hand-held rock drill is relatively light, generally below 25kg, and it is operated by hand when working. A variety of small diameter and shallow holes can be drilled, generally ...

Oil Lubricator for Rock Drill/Jack Hammer Oil Lubricator connect to Pneumatic Drill, filtering the inner construction of Jackhammer to make drill work well, more efficiency.

Scope of application YT28 is a heavy-duty pusher leg Rock Drill featuring high efficiency and low air consumption is primarily designed for drilling in mines, hydro-power stations, and road ...

Notice in operation it has been filled with antirust oil. It should be washed and the air pipe to flexible and credible. The oiler should be filled with oil all parts are flexible and credible. The oiler ...

Product Safety Information Intended Use: Model YT28 Air Percussive Rock Drills are mainly used for tunnelling work in mines and drilling holes in medium and hard rock. They are also ...

Air Leg Rock Drill YT28 is a kind of high efficiency air leg rock drill machinery. It is mainly used for digging into mine laneway and blasting holes in all drilling works. It is indispensably importance ...

YT28 air leg rock drill is mainly used for blasting holes and other drilling works in a quarries, railway construction, water conservancy construction and defence project facility. Further, it is ...

The drill should not be run without proper lubrication (recommended lube oil N46 and N22, Chinese National Standard GB443-84). After operation, first turn off ...

FY250 Oil Lubricator Oiler For Yt29 Rock Drill Yt27 Yt28 - Buy Oil Lubricator, Oiler, Oil Filler Product on Alibaba FY250 oil lubricator oiler for yt29 rock drill yt27 yt28

The oiler should be filled with lubrication and adjust the oil flux. 3 Before start the machine should check whether all parts are flexible and credible. The oiler should be filled with lubrication and ...

The Internal Combustion Rock Drill Type YN30A is a portable rock drilling machine, composed of a small



What oil should be used for the oiler of the yt28 rock drill

petrol engine, an air compressor and a rock drill. During operation, rock powder is ...

Analysis on the use of rock drills¹. The machine has anti-rust oil when it leaves the factory. It should be disassembled and cleaned before use. When ...

Rock Drill YT28 Product Description: The Products are mainly used in construction sites, various types of mines, railways, water conservancy ...

Description of YT28 Pneumatic rock drilling machine: The YT28 rock drill machine is a kind of high-efficiency air leg rock drill machinery. It is mainly used for ...

When using the YT28 rock drill, pay attention to the following items: 1. The YT28 JACKLEG DRILL has anti-rust oil when it leaves the factory, it should be disassembled and ...

The importance of using the correct rock drill oil cannot be overstated. Substituting it with a generic lubricant can lead to premature wear, increased downtime, reduced drilling ...

The rock drill is a kind of high efficiency air leg rock drill machinery. It is mainly used for digging into mine laneway and blasting holes in all drilling works. It is indispensably importance machine ...

YT28 Air-leg Rock Drill most fit for drilling horizontal and inclined blast holes in medium-hard and hard rock with a hardness of $f=8\sim 18$. It may also be used ...

The Rock Drill is equipped with lubricator FY200C. Secoroc YT28 is intended to be used together with pusher leg FT160BC and FT160BD for different tunneling and work conditions.

Page 6: Operation Operation Using the rock drill for the first time When the rock drill arrives from the factory, the inside of the tool is coated with heavy oil to ...

The BD-YT28 Air Leg Rock Drill is a product that adopts all the latest design technology. It is an efficient, energy saving rock drill. The BD-YT28 Air Leg rock drill has lower noise, higher ...

This machine is equipped with FY200B lubricator with transparent casing to ensure good lubrication. Rock drill skills¹) When the rock drill is in use, the ...

YT28 Air-leg Rock Drill most fit for drilling horizontal and inclined blast holes in medium-hard and hard rock with a hardness of $f=8\sim 18$. It may also be used with for making roof-bolting holes. ...

The weight of the hand-held rock drill is relatively light, generally below 25kg, and it is operated by hand when working. A variety of small diameter and shallow ...



What oil should be used for the oiler of the yt28 rock drill

The YT28 air-leg rock drill is most suitable for drilling horizontal or inclined blastholes in medium-hard or hard rock. It can be used with FT160BC or ...

It may also be for making roof bolting holes. The drill is an important instrument in mining, railway, communication and water conservancy projects. May be used together with FT160BC or ...

The drill is an important instrument in mining, railway, communication and water conservancy projects. May be used together with FT160BC or FT160BD Air-leg and FY200B Line Oiler ...

Web: <https://www.staskowachata.pl>